TECHNICAL DATA SHEET





METAL ANTI-CORROSION PAINT

Its a spray paint, a protective coat against corrosion, a primer and a final coat in one go. Gives old, shabby metals an attractive and durable, satin glossy shine. For metal exposed to corrosion (iron, steel sheet), e.g. garden fences, gates, banisters, gardening tools, playground devices (e.g. swings) and many others. Suitable for interior and exterior applications.

Area of use:

The paint is intended for metal exposed to corrosion (iron, steel sheet), e.g. garden fences, gates, banisters, gardening tools, playground devices (e.g. swings) and many others.

Advantages:

- · Four in one primer, rust protection, paint and varnish
- · Very good anti-corrosion properties
- Excellent adhesion and coverage
- · Weatherproof, for indoor and outdoor use
- · Easy to use and apply
- Ideal for DIY enthusiasts, craftsmen and industrial users

Spray passes:

2-3 cross layers, spraying distance: 30 cm.

Drying times:

- Dust free: in around 30 min.
- Touch dry: in around 60 min.
- Complete dryness: in around 24 h.

Yield:

1,2-1,5 m² (from one 400 ml. can, one layer).

Usage:

The surface must be clean, dry and grease-free. Shake the can vigorously for 1 minute. Apply thin layers from a distance of about 30 cm. Keep a 10-15 min. interval between layers (at least 2). The paint dries completely after 24 hours. After use, turn the can upside down and spray the valve until empty (about 3 sec.).

Base: alkyd resins

Package: 400 ml



TECHNICAL DATA SHEET



Safety	data	she	et:
Daice	, auta	2116	

presented separately.

Protection measures:

wear personal protection equipment (gloves / goggles). For more information, see safety data sheet.

Storage:

store verticaly at +10 °C...+25 °C temperature and relative air humidity of max. 60%.

Shelf life:

10 years if appropriate storage provided.

Color tones:

Art. nr.	Color	Gloss level
26-8-3-003	Gold	Satin

