TECHNICAL DATA SHEET





Inral LACQUER acrylic lacquer

Quick-drying acrylic lacquer spray. For use on metal, wood, glass, ceramic, plastic and painted surfaces. Forms a clear, hard surface resistant to heat, cracking, scratching and peeling.

Area of use

For use on metal, wood, glass, ceramic, plastic and painted surfaces

Advantages

- Fast drying
- High gloss or Matte
- Good coverage (depending on the colour)
- · Hard and flexible coating
- Resistant to weather conditions
- · Lead- and chromate-free
- No ozone-depleting substances

Spray passes:

2-3 cross layer, spraying distance: 30 cm.

Drying times:

- Touch dry: about 20 min.
- Other layers: after 20 min.

Yield:

2 m² (from one 400 ml. can, one layer).

Usage:

Clean and degrease the surface. Shake the vial vigorously for 1 min. Spray evenly from a distance of 30 cm. Most effective when applying several thin layers intermittently. When finished, turn the vial upside down and squeeze out the atomizer, holding it for a few seconds.

Base: acrylic resins

Package: 400 ml



TECHNICAL DATA SHEET



Safety	data	she	et:
Daice	, auta	2116	

presented separately.

Protection measures:

wear personal protection equipment (gloves / goggles). For more information, see safety data sheet.

Storage:

Store upright in a dry place at +5°C to +25°C. Do not expose the cans to direct sunlight or heat above 50°C.

Shelf life:

10 years if appropriate storage provided.

Color tones:

Art. nr.	Color	Gloss level
26-7-0-003	Clear	Matte

