



**Base:**  
vinyl

**Package:**  
400 ml

## Inral ZINC GROUND ANTI-CORROSION spray paint

Zinc accounts for about 85 % of the dry weight of the coating forming a protective layer on iron compound surfaces. The primer layer can be coated with acrylic, polyvinyl or alkyd paints. For surfaces heated up to +60 °C..

### Area of use:

Corrosion protection paint for steel and cast iron structures, metal parts, machinery and miscellaneous equipment, industrial installations, building surfaces, energy structures, poles, streetlights, fences, storage sheds, fences, etc.

### Advantages:

- Fast-drying with perfect coating and adhesive properties for steel bases
- Provides cathodic protection to metal
- Resilient to effects of industrial, maritime, urban and rural environments
- Resilient to temperatures from -20 to 60 (periodically to 80)°C
- Lead- and chromates-free
- Ozone-friendly oxes etc.

### Spray passes:

1-2 cross layer, spraying distance: 30 cm.

### Drying times:

- Touch dry: about 20 min.
- Other layers: after 60 min.
- Other products: after 3h

### Yield:

2 m<sup>2</sup> (from one 400 ml. can, one layer).

### Usage:

Clean and degrease the surface. Shake the can vigorously for 1 min. Spray evenly on the surface at a distance of 30 cm. Most effective when applied as a thin coat, with breaks, in several layers. Apply water-based paint no sooner than after 1 day. When finished, turn the can upside down and clean the pulveriser by holding it down for a few seconds.

## Safety data sheet:

presented separately.

## Protection measures:

wear personal protection equipment (gloves / goggles). For more information, see safety data sheet.

## Storage:

Store upright in a dry place at +5°C to +25°C. Do not expose the cans to direct sunlight or heat above 50°C.

## Shelf life:

10 years if appropriate storage provided.

## Color tones:

Art. nr.	Color	Gloss level
26-7-2-009	Zinc	Matte