# **TECHNICAL DATA SHEET**





# Inral PLASTIC GROUND spray paint

Primer spray for plastic surfaces. PLASTIC PRIMER provides particularly excellent adhesion between polypropylene-based plastics (polyethylene EPDM, some ABS types) and other coated surfaces. Ideal for indoor and outdoor applications.

#### Area of use:

For use on cars, motorcycles, garden furniture or any other plastic surface.

#### **Advantages:**

- Rapid drying, colourless
- Excellent adhesion to polypropylene surfaces
- Ensures excellent adhesion of topcoat paint or enamel paint
- Lead- and chromate-free
- Ozone-friendly

#### **Spray passes:**

1-2 cross layer, spraying distance: 30 cm.

### **Drying times:**

- Touch dry: about 5 min.
- Other layers: after 10 min.

#### Yield:

2 m² (from one 400 ml. can, one layer).

#### **Usage:**

Wipe and degrease the surface. Shake the can vigorously for 1 min. Spray evenly on the surface at a distance of 30 cm. Most effective when applied as a thin coat, with breaks, in several layers. When finished, turn the can upside down and clean the pulveriser by holding it down for a few seconds.

**Base:** chlorinated polyolefin

Package: 400 ml



# **TECHNICAL DATA SHEET**



Safety	data	she	et:
Daice	, auta	2116	

presented separately.

# **Protection measures:**

wear personal protection equipment (gloves / goggles). For more information, see safety data sheet.

# **Storage:**

Store upright in a dry place at +5°C to +25°C. Do not expose the cans to direct sunlight or heat above 50°C.

# **Shelf life:**

10 years if appropriate storage provided.

# **Color tones:**

Art. nr.	Color	Gloss level
26-7-2-010	Clear	Matte

