TECHNICAL DATA SHEET





Inral FLUOMARKER spray paint

Acrylic fluorescent marking spray paint is used in the construction industry, for marking (trees, bridges, roads, etc.), planning and marking of roads, sports fields. The paint fades spontaneously under outdoor conditions within 3 months. Increased pigment content also allows using for fine lines that will be clearly visible. The pack is designed to be used at any 360° angle, to easily reach any point. For indoor and outdoor applications. Suitable for marking virtually any object and surface: including asphalt, concrete, pipes and even soil or snow. Free of lead or chromium compounds, does not deplete the ozone layer.

Area of use:

For marking virtually any object and surface: including asphalt, concrete, pipes and even soil or snow.

Advantages:

- · Matt coating with fluorescent effect in daylight
- · Basic colours: red, orange, yellow, green and pink
- · Photo-luminescent when exposed to UV light
- · Lead- and chromate-free
- · Ozone-friendly
- No reflective properties or fluorescent effects in the dark
- Upside down spraying

Durability of the effect:

Paints fade away within 3-6 months, depending on the indoor or outdoor use, type of surface, thickness, environmental impacts and UV radiation.

Drying times:

- Touch dry (at 20°C): about 5 min.
- · Applying another layer: 5 min.

Yield:

2 m² (from one 500 ml. can, one layer).

Usage:

The optimal temperature of a container is $15 \div 25$ °C. Shake the can vigorously for 1 min. Spray perpendicular to the surface at a distance of 1-2 cm for a thin line or 5-20 cm for a thicker line or dot. To decorate, spray at a distance of 20 cm in 2-4 layers every few minutes. Product usage from +5 till +30 °C.

Base: acrylic polymer

Package: 500 ml



TECHNICAL DATA SHEET



Safet	v data	sheet	•
Duice	,	211666	۰

presented separately.

Protection measures:

wear personal protection equipment (gloves / goggles). For more information, see safety data sheet.

Storage:

Store upright in a dry place at +5°C to +25°C. Do not expose the cans to direct sunlight or heat above 50°C.

Shelf life:

5 years if appropriate storage provided.

Color tones:

Art. nr.	Color	Gloss level
26-7-5-010	Green	Matte

