



**Base:**  
modified alkyd

**Package:**  
400 ml

## Inral spray paint ROOF SPRAY

Fast-drying spray paint for repair of defects in metal roofing tiles, rainwater pipes and gutters. The enamel creates a hard surface resistant to temperature, cracking, scratching and peeling.

### Area of use:

For roofing and guttering, repairs of defects.

### Advantages:

- Quick-drying, high gloss, high opacity
- Various colors available, including selected colors from the RAL palette.
- Good adhesion to the substrate
- Resistant to sunlight exposure and rainfall
- Does not contain lead or chromate compounds
- Does not contain any substances damaging to the ozone layer

### Spray passes:

2-3 cross layers, spraying distance: 30 cm.

### Drying times:

- Touch dry: about 20 minutes
- Wet on wet: up to 1 hour
- Overcoating: before 6 hours

### Yield:

2 m<sup>2</sup> (from one 400 ml. can, one layer).

### Usage:

Clean, degrease and coat with INRAL GROUND anti-corrosion primer. Shake the can vigorously for 1 min. Spray evenly on the surface at a distance of 30Cm. Most effective when applied as a thin coat, with breaks, in several layers. When finished, turn the can upside down and clean the pulveriser by holding it down for a few seconds

## Safety data sheet:

presented separately.

## Protection measures:

wear personal protection equipment (gloves / goggles). For more information, see safety data sheet.

## Storage:

Store upright in a dry place at +5°C to +25°C. Do not expose the cans to direct sunlight or heat above 50°C.

## Shelf life:

10 years if appropriate storage provided.

## Color tones:

| Art. nr.   | Color         | Gloss level |
|------------|---------------|-------------|
| 26-7-7-009 | Graphite grey | Glossy      |