

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 15.11.2022 Revision: 15.11.2022

Version number 1

INRAL

TRADE NAME: INRAL METAL PAINT 4IN1 ANTHRACITE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: INRAL METAL PAINT 4IN1 ANTHRACITE
(Article number) product ID.: 26-8-3-002

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU21 Consumer uses: Private households / general public / consumers

Application of the substance / the mixture: painting
Uses advised against No further relevant information available.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

UAB TEGRA STATE
Savanoriu ave.178A, LT-03154 Vilnius, LITHUANIA
Tel.: +37052661167
www.tegrastate.eu
E-mail: info@tegragroup.eu

Further information obtainable from: Product safety department

1.4 Emergency telephone number:

112
National Poisons Information Service, Birmingham
Tel.: 844 892 0111
Lithuania Poisons Control and Information Bureau, Vilnius
Tel.: +370 5 236 20 52 / +370 687 533 78

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 15.11.2022 Revision: 15.11.2022

Version number 1

INRAL

TRADE NAME: INRAL METAL PAINT 4IN1 ANTHRACITE

Hazard pictograms



GHS02

GHS07

Signal word Danger

Hazard-determining components of labelling:

n-butyl acetate
4-morpholinecarbaldehyde
butanone
ethyl acetate
cobalt(II) 2-ethylhexanoate

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P271 Use only outdoors or in a well-ventilated area.
P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Without adequate ventilation, explosive atmosphere/gas mix may be created.
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 15.11.2022 Revision: 15.11.2022

Version number 1

INRAL

TRADE NAME: INRAL METAL PAINT 4IN1 ANTHRACITE

SECTION 3: Composition/information on ingredients

3.1 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	25-<50%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	10-<25%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx	butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	5-<10%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	5-<10%
CAS: 4394-85-8 EINECS: 224-518-3	4-morpholinecarbaldehyde ⚠ Skin Sens. 1, H317	1-<2,5%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-<2,5%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29-xxxx	cobalt(II) 2-ethylhexanoate ⚠ Repr. 1A, H360F; ⚠ Aquatic Acute 1, H400; ⚠ Eye Irrit. 2, H319; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	<0,1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 15.11.2022 Revision: 15.11.2022

Version number 1

The logo for INRAL, featuring the word "INRAL" in a bold, white, sans-serif font. To the right of the text is a stylized yellow and orange circular graphic element.

TRADE NAME: INRAL METAL PAINT 4IN1 ANTHRACITE

SECTION 5: Firefighting measures

- 5.1 Extinguishing media -**
Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- 5.3 Advice for firefighters**
Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- 6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Information about fire - and explosion protection:
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- 7.2 Conditions for safe storage, including any incompatibilities**
Storage:
Requirements to be met by storerooms and receptacles:
Observe official regulations on storing packagings with pressurised containers.
Information about storage in one common storage facility: Not required.
Further information about storage conditions: None.
- 7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters**

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 15.11.2022 Revision: 15.11.2022

Version number 1

INRAL

TRADE NAME: INRAL METAL PAINT 4IN1 ANTHRACITE

Ingredients with limit values that require monitoring at the workplace:	
115-10-6 dimethyl ether	
WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
123-86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
78-93-3 butanone	
WEL	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
141-78-6 ethyl acetate	
WEL	Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm
1330-20-7 xylene, mixture of isomers	
WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
Ingredients with biological limit values:	
78-93-3 butanone	
BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one
1330-20-7 xylene, mixture of isomers	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:



Jei tirpiųjų medžiagų koncentracija viršija MAK ribines vertes, reikia užsidėti tam tikslui skirtą kvėpavimo takų apsauginę įrangą.

Puskaukė su mažiausiai filtravimo klasės A1P2 kombinuojamu filtru arba atskirai teikiamo oro kvėpavimo takų apsauginė įranga.

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 15.11.2022 Revision: 15.11.2022

Version number 1

INRAL

TRADE NAME: INRAL METAL PAINT 4IN1 ANTHRACITE

Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves Nitrile rubber, NBR

Penetration time of glove material

Gloves must be changed after every contamination.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

Eye/face protection

Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Aerosol

Colour:

According to product specification

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Undetermined.

Boiling point or initial

boiling point and boiling

range

-24.9 °C

Flammability

Not applicable.

Lower and upper explosion limit

Lower:

1.2 Vol % (123-86-4 n-butyl acetate)

Upper:

18.6 Vol % (115-10-6 dimethyl ether)

Flash point:

<0 °C

Ignition temperature:

460 °C (141-78-6 ethyl acetate)

Decomposition temperature:

Not determined.

pH

Not determined.

Viscosity:

Kinematic viscosity

Not determined.

Dynamic:

Not determined.

Solubility

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 15.11.2022 Revision: 15.11.2022

Version number 1

INRAL

TRADE NAME: INRAL METAL PAINT 4IN1 ANTHRACITE

water: Not miscible or difficult to mix.
Partition coefficient
n-octanol/water (log value) Not determined.
Vapour pressure at 20 °C: 3,400 hPa (115-10-6 dimethyl ether)
Density and/or relative density
Relative density Not determined.
Vapour density Not determined.

9.2 Other information

Appearance:

Form: Aerosol

Important information on protection of health and environment, and on safety.

Auto-ignition temperature:

Product is not selfigniting.

Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Not determined.

Solvent content:

Organic solvents:

65.9 %

With propellant gas. Content given by weight.

VOC (EU)

65.87 %

Solids content:

34.0 %

Change in condition

Evaporation rate

Not applicable.

Information with regard to physical hazard classes

Explosives

Void

Flammable gases

Void

Aerosols

Extremely flammable aerosol. Pressurised container:
May burst if heated.

Oxidising gases

Void

Gases under pressure

Void

Flammable liquids

Void

Flammable solids

Void

Self-reactive substances and mixtures

Void

Pyrophoric liquids

Void

Pyrophoric solids

Void

Self-heating substances and mixtures

Void

Substances and mixtures,

which emit flammable

gases in contact with water

Void

Oxidising liquids

Void

Oxidising solids

Void

Organic peroxides

Void

Corrosive to metals

Void

Desensitised explosives

Void

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 15.11.2022 Revision: 15.11.2022

Version number 1

INRAL

TRADE NAME: INRAL METAL PAINT 4IN1 ANTHRACITE

SECTION 10: Stability and reactivity

- 10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability**
Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid** No further relevant information available.
- 10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation May cause an allergic skin reaction.

STOT-single exposure May cause drowsiness or dizziness.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- 12.1 Toxicity**
Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability** No further relevant information available.
- 12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment**
PBT: Not applicable.
vPvB: Ikke relevant.
- 12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects**
Additional ecological information:
General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 15.11.2022 Revision: 15.11.2022

Version number 1

INRAL

TRADE NAME: INRAL METAL PAINT 4IN1 ANTHRACITE

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN1950

14.2 UN proper shipping name

ADR 1950 AEROSOLS
IMDG AEROSOLS
IATA AEROSOLS, flammable

14.3 Transport hazard class(es)

ADR



Class 2.1 Gases.
Label 2.1

IMDG, IATA



Class 2.1 Gases.
Label 2.1

14.4 Packing group

ADR, IMDG, IATA Void
not classified

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user Warning: Gases. Hazard identification number (Kemler code): -

EMS Number:
Stowage Code

not classified
F-D,S-U
SW1 Protected from sources of heat.
SW2 Clear of living quarters.
SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

Segregation Code

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 15.11.2022 Revision: 15.11.2022

Version number 1

INRAL

TRADE NAME: INRAL METAL PAINT 4IN1 ANTHRACITE

For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

14.7 Maritime transport in bulk according to IMO instruments

Transport/Additional information:

ADR

Limited quantities (LQ)

Excepted quantities (EQ) Code:

Transport category

Tunnel restriction code

IMDG

Limited quantities (LQ)

Excepted quantities (EQ) Code:

UN "Model Regulation":

Not applicable.

1L

E0

Not permitted as Excepted Quantity

2

D

1L

E0

Not permitted as Excepted Quantity

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC: <840g/l

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P3a FLAMMABLE AEROSOLS

Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

National regulations:

Technical instructions (air):

Class	Share in %
NK	50-100

Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 15.11.2022 Revision: 15.11.2022

Version number 1

The logo for INRAL, featuring the word "INRAL" in a bold, white, sans-serif font. To the right of the text is a stylized yellow and orange circular graphic element.

TRADE NAME: INRAL METAL PAINT 4IN1 ANTHRACITE

H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H360F May damage fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.
EUH018 In use may form flammable/explosive vapour-air mixture.
EUH066 Repeated exposure may cause skin dryness or cracking.

Department issuing SDS: Product safety department

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

: Aerosols – Category 3

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Repr. 1A: Reproductive toxicity – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* **Data compared to the previous version altered.**