

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: INRAL Camouflage
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture: painting
- · Uses advised against No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

UAB TEGRA STATE

- · Savanoriu ave 178A, LT-03154 Vilnius, LITHUANIA
- · Tel.:+37052661167
- · www.tegrastate.eu
- · E-mail: info@tegragroup.eu
- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number:
- · national:

National Poisons Information Service, Birmingham

Tel.: 844 892 0111

· K-Nr. 0001

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02

GHS07

(Contd. on page 2)

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: INRAL Camouflage

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labelling:

acetone

n-butyl acetate

2-methoxy-1-methylethyl acetate

· Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

smoking.

Do not spray on an open flame or other ignition source. P211

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Call a POISON CENTER/doctor if you feel unwell. P312 P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· Additional information:

Without adequate ventilation, explosive atmosphere/gas mix may be created.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	25-<50%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	10-<25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (containing ≤ 0,1 % butadiene (203-450-8)) ♦ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	5-<10%
CAS: 9004-70-0 Reg.nr.: no Reach No. availlable	nitrocellulose with water(not less than 25% water, by mass) Expl. 1.1, H201	5-<10%
	· ·	(Contd. on pag

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: INRAL Camouflage

		(Contd. of page
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane (containing ≤ 0,1 % butadiene (203-450-8)) ♦ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	2.5-<5%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319	2.5-<5%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-<2.5%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx	butanone ♠ Flam. Liq. 2, H225; ♠ Eye Irrit. 2, H319; STOT SE 3, H336	<1%
CAS: 7397-62-8 EINECS: 230-991-7 Reg.nr.: 01-2119514685-36-xxxx	butyl glycollate ♦ Repr. 2, H361; ♦ Eye Dam. 1, H318	<1%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	<1%
CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38-xxxx	butan-1-ol Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335; STOT SE 3, H336	<1%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40-xxxx	trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<i>≥</i> 0.025-<0.25%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: INRAL Camouflage

(Contd. of page 3)

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- \cdot 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

$106-97-8 \ butane \ (containing \le 0.1 \% \ butadiene \ (203-450-8))$

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

(Contd. on page 5)

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: INRAL Camouflage

	(Contd. o	of pag
108-63	5-6 2-methoxy-1-methylethyl acetate	
WEL .	Short-term value: 548 mg/m³, 100 ppm	
	Long-term value: 274 mg/m³, 50 ppm	
	Sk	
64-17-	-5 ethanol	
WEL .	Long-term value: 1920 mg/m³, 1000 ppm	
1330-2	20-7 xylene, mixture of isomers	
WEL .	Short-term value: 441 mg/m³, 100 ppm	
	Long-term value: 220 mg/m³, 50 ppm	
	Sk; BMGV	
78-93-	-3 butanone	
WEL .	Short-term value: 899 mg/m³, 300 ppm	
	Long-term value: 600 mg/m³, 200 ppm	
,	Sk, BMGV	
100-4	1-4 ethylbenzene	
WEL ,	Short-term value: 552 mg/m³, 125 ppm	
	Long-term value: 441 mg/m³, 100 ppm	
	Sk	
71-36-	-3 butan-1-ol	
WEL .	Short-term value: 154 mg/m³, 50 ppm	
,	Sk	
Ingrea	dients with biological limit values:	
1330-2	20-7 xylene, mixture of isomers	
BMGV	V 650 mmol/mol creatinine	
	Medium: urine	
	Sampling time: post shift	
	Parameter: methyl hippuric acid	
78-93-	-3 butanone	
BMGV	V 70 μmol/L	
	Medium: urine	
	Sampling time: post shift	
	Parameter: butan-2-one	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

(Contd. on page 6)

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: INRAL Camouflage

(Contd. of page 5)

· Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

· Eye/face protection

Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range -44 °C

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: 1.7 Vol %

• Upper: 13 Vol %

• Flash point: <0 °C

• Auto-ignition temperature: 365 °C (106-97-8 butane (containing $\leq 0,1$ % butadiene

(203-450-8)))

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosity
 Dynamic:
 Not determined.
 Not determined.

· Solubility

• water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
Vapour pressure at 20 °C:
Vapour pressure at 50 °C:
800 hPa

· Density and/or relative density

Relative density
 Vapour density
 Not determined.

(Contd. on page 7)

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: INRAL Camouflage

(Contd. of page 6)

· 9.2 Other information

· Appearance:

· Form: Aerosol

Important information on protection of health and

environment, and on safety.

· Ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Not determined.

· Solvent content:

• Organic solvents: 85.9 %

With propellant gas. Content given by weight.

• Water: 0.0 %
 • VOC (EU) (<840g/l)
 • Solids content: 13.6 %

· Change in condition

• Evaporation rate Not applicable.

· Information with regard to physical hazard classes

Explosives VoidFlammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

· Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

GB

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: INRAL Camouflage

(Contd. of page 7)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

 Dermal
 LD50
 97,085 mg/kg (rabbit)

 Inhalative
 LC50/4 h
 534 mg/l (rat)

- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

556-67-2 octamethylcyclotetrasiloxane

List II; III

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Ikke relevant.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informati	ion
---------------------------------	-----

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable

(Contd. on page 9)

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: INRAL Camouflage

(Contd. of page 8) · 14.3 Transport hazard class(es) $\cdot ADR$ · Class 2 5F Gases. · Label 2.1 · IMDG, IATA 2.1 Gases. · Class · Label 2.1 · 14.4 Packing group Void · ADR, IMDG, IATA not classified · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): not classified · EMS Number: F-D,S-USW1 Protected from sources of heat. · Stowage Code SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 · Segregation Code litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. · Transport/Additional information: · Limited quantities (LQ) · Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity · Transport category 2 · Tunnel restriction code · Limited quantities (LQ) 1L(Contd. on page 10)

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: INRAL Camouflage

	(Contd. of page 9)
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l
- · Poisons Act

· Poisons Act	
· Regulated explosives precursors	
None of the ingredients is listed.	
· Regulated poisons	
None of the ingredients is listed.	
· Reportable explosives precursors	
67-64-1 acetone	Listed
· Reportable poisons	
50-00-0 formaldehyde	5%

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet may only be passed on to third parties for the manufacturer's brands.

· Relevant phrases

- H201 Explosive; mass explosion hazard.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.

(Contd. on page 11)

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

Trade name: INRAL Camouflage

(Contd. of page 10)

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure. H373

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH018 In use may form flammable/explosive vapour-air mixture.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Product safety department

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Expl. 1.1: Explosives – Division 1.1

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

: Aerosols – Category 3

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

* Data compared to the previous version altered.