

REINFORCED TAPE PLUS For plastering work

DESCRIPTION:

General purpose duct tape with a good adhesive power. A synthetic rubber based duct tape with a flexible, easily mouldable and waterproof PE coated fabric which is tearable by hand. Reinforced tape plus has a strong initial tack and a good adhesive power.



APPLICATION:

Reinforced tape plus is perfectly suitable for adhesion on smooth and rough surfaces such as stainless steel, polyethylene, glass and wood and is used for general applications such as repairing, sealing holding, protecting and bundling.

TECHNICAL CHARACTERISTICS:

Carrier type	PE coated fabric
Adhesive type	Hotmelt / synthetic rubber
Overall thickness [µm]	170
Mesh density (fabric)	32
Adhesion on steel [N/25mm]	20
Rolling ball tack [cm]	< 1
Tensile strength [N/25 mm]	75
Service temperature [°C]	-10 up to +75

SIZES:

Width [mm]: 38, 48
Length [m]: 33
Core [mm]: 76

STORAGE CONDITIONS:

Store in a cool dry place away from sunlight and direct heat sources. As far as the storage conditions are respected, the product is guaranteed 12 months.

DISCLAIMER:

All statements, technical information and product recommendations are based on tests in our laboratories we believe to be reliable. In all cases the user should however determine the suitability of the product for his intended use and user assumes all risk and liability whatsoever in connection therewith. Neither seller or manufacturer shall be liable for any loss or damage - direct, incidental or consequential - arising from the use of the product. Details of test methods are available on request.