

TECHNICAL DATA SHEET**FOME FLEX HARDENED FOAM REMOVER**

Used to remove hardened PU mounting foam from tools and surfaces. Dissolve hardened foam for easy removal.

Advantages

- Dissolves hardened PU foam.
- Easy to use.
- A convenient nozzle is included.
- Cleans various surface treatment materials.

Taikymo sritys

Used to remove hardened mounting foam from tools and other surfaces. For removing hardened foam from doors and windows frames, windowsills and other surfaces that have become dirty during construction and decoration works. Cleaning of varnishes, paints and other processing materials.

Technical Specifications

Indicator	Units	Value
Colour		Transparent
Base material		Solvent: gamma - butyrolactone
Storage temperature	°C	+5 ... +25
Application temperature	°C	+5 ... +30
Volume	ml	320

Directions of Use

Before use, test the compatibility of the cleaner on an inconspicuous spot on the surface. Shake the can, spray the product on the hardened foam. Avoid spraying on adjacent surfaces, as the product dissolves various treated sensitive surfaces. Allow the foam to soften for about 10 minutes. and then remove the foam mechanically.

Storage conditions

Store upright in a dry place at +5 °C to +25 °C. Expiry date - 18 months from date of manufacture, subject to storage regulations. Protect canisters from direct sunlight and heat above 50 °C.

Packaging

520 ml aerosol canister, volume 320 ml, 12 pcs. in per box.



TECHNICAL DATA SHEET

Health & Safety

Product Safety Data Sheet must be read and understood before use. These are available on request.

Waste management

Completely empty the packaging and dispose of properly.