

Fome Flex AQUASTOP

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Trade name: Fome Flex AQUASTOP

1.2 Relevant identified uses of the substance or mixture and uses advised against

No data available

Application of the substance / the mixture Sealant

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

UAB TEGRA STATE

Savanoriu ave 178A, LT-03154 Vilnius, LITHUANIA

Tel.:+37052661167

www.tegrastate.eu

E-mail: info@tegragroup.eu

1.4 Emergency telephone number

European emergency number: 112 (24h)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS07

Signal word Warning

Hazard-determining components of labelling:

n-butyl acetate

Hydrocarbons, C9-unsaturated, polimerized

Hazard statements

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

Precautionary statements

P102 Keep out of reach of children.

P261 Avoid breathing vapours.

Fome Flex AQUASTOP

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Results of PBT and vPvB assessment





PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.1 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 64742-47-8 EINECS: 265-149-8 Reg.nr.: 01-2119484819-18-XXXX	Distillates (petroleum), hydrotreated light  Asp. Tox. 1, H304	<22.1%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-XXXX	n-butyl acetate  Flam. Liq. 2, H225;  STOT SE 3, H336, EUH066	<21.1%
CAS: 71302-83-5 Reg.nr.: 01-2119555292-40-XXXX	Hydrocarbons, C9-unsaturated, polymerized  Skin Sens. 1, H317; Aquatic Chronic 3, H412	<4.1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

After skin contact:

Wash with plenty of water or water and soap. In cases of sickness seek medical advice (show label if possible).

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed Headache.

Fome Flex AQUASTOP

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

In case of fire, the following can be released:

Carbon monoxide (CO).

5.3 Advice for firefighters

Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device.

Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Keep away from ignition sources.

6.2 Environmental precautions: Do not allow to enter sewers / surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 13 for disposal information.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation / exhaustion at the workplace.

Keep away from heat and direct sunlight.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fome Flex AQUASTOP

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Store at temperature from 5°C to 25°C.

Keep container tightly sealed.

7.3 Specific end use(s) No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:		
CAS: 123-86-4 n-butyl acetate		
WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm	
DNELs		
CAS: 123-86-4 n-butyl acetate		
Oral	DNEL	2 mg/kg/day (General population, consumers)
Dermal	DNEL	6 mg/kg/day (General population, consumers) 11 mg/kg/day (Workers)
Inhalative	DNEL	35.7 mg/m ³ (General population, consumers) 300 mg/m ³ (Workers)
CAS: 71302-83-5 Hydrocarbons, C9-unsaturated, polimerized		
Oral	DNEL	0.33 mg/kg/day (General population, consumers)
Dermal	DNEL	1.67 mg/kg/day (General population, consumers) 4.7 mg/kg/day (Workers)
Inhalative	DNEL	0.58 mg/m ³ (General population, consumers) 3.3 mg/m ³ (Workers)
PNECs		
CAS: 123-86-4 n-butyl acetate		
(freshwater)	0.18 mg/l (Aquatic Organisms)	
(sea water)	0.018 mg/l (Aquatic Organisms)	
(freshwater sediments)	0.981 mg/kg (Aquatic Organisms)	
(sea water sediments)	0.098 mg/kg (Aquatic Organisms)	
(soil)	0.09 mg/kg (Terrestrial Organism)	
CAS: 71302-83-5 Hydrocarbons, C9-unsaturated, polimerized		
(freshwater)	0.0258 mg/l (Aquatic Organisms)	
(sea water)	0.00258 mg/l (Aquatic Organisms)	
(freshwater sediments)	1,960 mg/kg (Aquatic Organisms)	
(sea water sediments)	196 mg/kg (Aquatic Organisms)	
(soil)	391 mg/kg (Terrestrial Organism)	

Fome Flex AQUASTOP

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Immediately remove all soiled and contaminated clothing.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Respiratory protection: Not necessary if room is well-ventilated.

Hand protection



Protective gloves

EN 374

Protective gloves and protective skin cream

Material of gloves

Polyethylene gloves.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ³ 0.020 mm.

Penetration time of glove material

Short-term exposure \geq 10 min (EN 374)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Safety glasses

EN 166

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour: Different according to colouring

Odour: Weak, characteristic

Melting point/freezing point: Not determined

Boiling point or initial boiling point and boiling range Not determined

Lower and upper explosion limit

Lower: Not determined

Upper: Not determined

Flash point: Not applicable

Viscosity:

Dynamic: Not determined

Fome Flex AQUASTOP

Solubility

water:	Insoluble
Vapour pressure:	Not applicable
Density and/or relative density	
Density:	Not determined
Particle characteristics	See item 3.

9.2 Other information

Appearance: No data available

Form: Paste

Important information on protection of health and environment, and on safety.

Explosive properties: Product is not explosive. However, formation of explosive air / vapour mixtures are possible.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid

Handle away from heat, ignition sources, sparks, ignition points, flames, static electricity.

10.5 Incompatible materials:

Strong oxidants.

Strong acids and bases.

Fome Flex AQUASTOP

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
CAS: 71302-83-5 Hydrocarbons, C9-unsaturated, polimerized		
Oral	LD50	> 2000 mg/kg (rat) (OECD 423)
Dermal	LD50	> 2000 mg/kg (rat) (OECD 402)
Inhalative	LC50	> 5 mg/l (rat) (OECD 403)
CAS: 123-86-4 n-butyl acetate		
Oral	LD50	10760 mg/kg (rat) (OECD 423)
Dermal	LD50	> 14000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50	23.4 mg/l (rat) (OECD 403)

Skin corrosion/irritation May produce an allergic reaction.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties
None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:	
CAS: 71302-83-5 Hydrocarbons, C9-unsaturated, polimerized	
EC50	54 mg/l / 48 h (daphnia) >100 mg/l / 72 h (algae)
LC50	25.8 mg/l / 96 h (fish)
CAS: 123-86-4 n-butyl acetate	
EC50	44 mg/l (daphnia)
LC50	18 mg/l (fish)

Fome Flex AQUASTOP

12.2 Persistence and degradability No data.

12.3 Bioaccumulative potential No data available.

12.4 Mobility in soil No data available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects No data available.

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Do not allow to enter surface or ground water.

Dispose of in a safe manner in accordance with local / national regulations.

Assigning a code from the waste catalogue depends on the sector, in which the user operates, as well as on arrangements made between the waste generator and a competent environment protection department.

Substance/mixture as a waste compound brings hazardous properties HP: 5

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, ADN, IMDG, IATA

Not applicable

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA

Not applicable

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class

Not applicable

14.4 Packing group

ADR, IMDG, IATA

Not applicable

14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user

Not applicable.

Fome Flex AQUASTOP

**14.7 Maritime transport in bulk according to
IMO instruments
UN "Model Regulation":**

Not applicable.

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

1907/2006/CE Regulation, UK REACH

1272/2008/CE Regulation, GB CLP

2020/878/UE Regulation

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Recommended restriction of use Information in the appropriate technical data sheet of product.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3