

TECHNICAL DATA SHEET

FOME FLEX HYDROPROTECT TAPE



Description

Joint reinforcement tape is intended for additional reinforcement in places where deformational cracking is possible, as well as in the joints of floors, walls and ceilings, internal and external corners, and pipe transitions. It is used together with the waterproofing membrane FOME FLEX HYDROPROTECT. The waterproofing tape is immersed in the first layer of the waterproofing membrane and covered with the second.

Benefits

- Indoor & Outdoor

Application

- Intended for additional reinforcement in places where deformational cracking is possible.
- For using in floor, wall and ceiling joints, internal and external corners and pipe transitions.
- Suitable for use together with a waterproofing membrane FOME FLEX HYDROPROTECT.

TECHNICAL DATA SHEET

Technical Data

Color	Neutral white
Sealing zone width	100 mm
Total thickness	300 µm
Weight	50 g/m ²
Max. longitudinal tensile force	115 N
Max. transverse tensile force	90 N

Method of use

SURFACE PREPARATION

The surface should be clean, smooth, dry, free of grease, mechanical damage and other particles that reduce adhesion.

APPLICATION

The product is ready to use. Prime the surface. Wait until it dries. Then apply the first layer of FOME FLEX HYDROPROTECT waterproofing membrane on the surface. Cut an appropriate length of FOME FLEX HYDROPROTECT TAPE and dip it into the first layer of applied membrane. Press firmly against the surface so that there are no wrinkles and the membrane is fully absorbed into the tape. Apply a second layer of membrane over the submerged tape to completely cover the tape. Apply the membrane to the tape with a roller, brush or trowel.

Remarks / Restriction

Protect the tape from mechanical damage.

Transport / Storage

The product is packed in 25 m. long rolls. Store in a dry, cool and closed space.

Safety and Health Precautions

All written or oral information, recommendations and instructions are given according to our best knowledge, tests and experience, in good faith and in compliance with manufacturer's principles. Each user of this material will make sure in every possible way, including verification of the final product in proper conditions, about suitability of the supplied materials for their intended purposes. The manufacturer is not liable for any losses incurred due to inaccurate or erroneous application of the manufacturer's materials.