



POINT 95

Glue for wooden constructions

A adhesive based on acrylic dispersion for bonding different building materials to porous surfaces such as concrete, gypsum, cement, bricks, particle board and cardboard. Once hardened, the adhesive forms a transparent and extremely durable seam. The adhesive seam from white becomes transparent after hardening.

Advantages

- Resistant to cold and moisture after hardening
- High adhesion force after hardening 28 kg / cm
- Forms a transparent seam
- Odorless, solvent free
- Non-flammable
- Elastic seam

Perfect adhesion with:



Wood



Concrete



Bricks



Gypsum



Ceramics



Cork



Polystyrene



Drywall

Areas of application

- Bonding of thermal and acoustic insulation materials.
- Gluing of decor and building elements.
- Laying of skirting boards, edging, panels and ceramic tiles.

Users manual

All surfaces must be free of dust, dry, clean, free of grease and oil. Cut off the end of the cartridge tip and screw the nozzle included in the kit onto it. Put the cartridge in gun-syringe and fill the nozzle with glue by pressing the gun trigger several times. Apply adhesive strips or strips to any adhesive surface points. Join the surfaces to be glued and press firmly. Correction time after use is 20-30 minutes. Application temperature +10 °C ... +30 °C.

TECHNICAL DATA SHEET

Technical Specifications

Indicator	Value
Colour	white,transparent after hardening
Base material	acrylic dispersion
Density (ISO 2811-1)	1.05 g / ml
Thermal resistance after hardening	-20 °C ... +60 °C
Working environment temperature	+10 °C ... +30 °C
Correction time	20-30 min
Full hardening time	72 hours
Tensile strength (adhesion force) (DIN 53504 S2)	28 kg / cm ²
Dry balance	54%
Consumption	200-300 g/m ²
Capacity	280 ml

Limitations

- Do not use on PE, PP, Teflon and bituminous surfaces.
- At least one of the surfaces must be absorbent.
- Protect from water until fully cured.

Packaging

280 ml plastic cartridge, in a box of 12 cartridges.

Storage conditions

Warranty shelf life - 24 months from the date of manufacture, if stored in the closed original packaging in a dry and cool place from +5 °C to +30 °C.

Safety instructions

The safety data sheets of the product must be read before use. Safety data sheets are available upon request from official distributors.

Waste management

Completely empty the package and dispose of as required.